

SA-FSC-3382 series Mechanical Seal with Gel Fiber Splice Closure Specification Ver 3.2

Description

SA-FSC-3382 Fiber Splice Closure is a dome closure with mechanical seal and gel, which are designed for all cable application environments such as duct, aerial, buried and man-hole. SA-FSC-3382 Splice Closure supports numerous functions as mid-span, branch and direct splice. Accommodated with flexible splice trays and varies accessories are available for many scenarios. Rigorous tests are performed to approve the best quality for network reliability.

Features


- New Designed mechanical seal with gel
- Simpler operation design to cancel the hoop
- Mid-span operation without cutting the cable
- Easy for re-entry and re-open
- Ideal fiber management design
- Protection level: IP68







Specifications

Technical Specification						
Style	Dome					
Dimensions(mm)	Ф 246 x 540					
Sealing Type	Mechanical seal with gel					
Protection Grade	IP68					
Cable ports	8	Gel Seal Module Support Φ3 – Φ25 mm				
Closure Max Capacity	Single fiber splicing	288f				
Splice Tray Capacity	Single fiber splicing per tray	48f				
Max No. tray installed	6 pcs					
Color	Black					
Installation	Aerial, wall, pole, manhole etc.					










Order Information - Main Product Kit Order P/N



Accessory list

MUST select component 1: Cable sealing parts

	Col module	D	Optical cable fixing
Item	Gel module	Dummy rod	bracket
φ21-φ25mm		I	
φ16-φ22mm		I	
φ12-φ18mm		I	





Order P/N of standard component 1 Note : Select the 7 types to match and meet all 8 holes positions.

Order P/N	#1	#2	#3	#4	#5	#6	#7	#8
SA-FSC-3382-ACC-GR2125 φ21-φ25mm	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0
φ21-φ2311111	1	1	1	1	1	1	□ 1	□ 1
SA-FSC-3382-ACC-GR1622	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0
φ16-φ22mm	1	□ 1						
G + FGG 2202 + GG GD1210	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0
SA-FSC-3382-ACC-GR1218 φ12-φ18mm	1	□ 1	□ 1	□ 1	□ 1	1	□ 1	□ 1



SA-FSC-3382-ACC-GR0714	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0
φ7-φ14mm	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1
SA-FSC-3382-ACC-GR0508	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0
φ5-φ8mm	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1
SA-FSC-3382-ACC-GR0306	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0
φ3-φ6mm	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1
SA-FSC-3382-ACC-GR0000	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0	□ 0
Dummy	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1	□ 1

Standard component 2: Accessories



Desiccant

Function: Dehumidification



Bare fiber protective tube (8m)

Function: Manage bare fibers



Black insulation tape

Function: Protect grounding wire



Cleaning tissue

Function: Clean the bare fibers



Nylon cable tie

Function: Tie up the bare fiber protective tube and the loose tubes



Splicing heat-shrinking protective

sleeve

Protect fiber splice contacts





Fixing module for the armored cable (double-hole)

Corresponding to gel seal module $(\phi 7-\phi 14mm)$



Fixing module for the armored cable (single-hole)

Corresponding to gel seal module $(\phi 12-\phi 25mm)$

Order Information - Optional Accessories

Product	Order P/N	Note
	SA-FSC-3382-ACC-AIV	Valve for gas charging and discharging
aptit (SA-FSC-3382-ACC-0001	Mounting bracket Hoop Expansion bolt for wall mounting
	SA-FSC-3382-ACC-0002	Mounting bracket Hoop for pole mounting
	SA-FSC-3382-ACC-0003	Aerial clasps for cable-messenger mounting
	SA-FSC-3382-ACC-0100	48F splice tray for fiber storage and splicing (suitable for 48F round cable or 48F ribbon cable)
三世人	SA-FSC-3382-ACC-CMF	Closure mounting fixture Fixed on the table so that the closure can be placed horizontally for operation